

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Bobcat	337	1.77	45	6.00		1.77	45	3.75		8.62
Bobcat	341	1.77	45	6.00		1.77	45	3.75		8.62
Bobcat	435									
Bobcat	442	1.97	50	7.28	7.28	1.97	50	7.28	7.28	10.82
Bobcat	X337C									
Bobcat	X341C									
Bobcat	zx125	1.97	50	8.70	8.71	1.97	50	8.70	8.71	11.41
Case	580M	1.75		10.00	10.12	1.50		5.00	5.12	13.93
Case	580M Series 2	1.75		10.00	10.12	1.50		5.00	5.12	13.93
Case	580M Super M	1.75		10.00	10.12	1.50		5.00	5.12	13.93
Case	580M Super M Series 2	1.75		10.00	10.12	1.50		5.00	5.12	13.93
Case	590M Super M	1.75		10.00	10.12	1.50		5.00	5.12	13.93
Case	590M Super M Series 2	1.75		10.00	10.12	1.50		5.00	5.12	13.93
Case	9007B	1.97	50	7.48	7.52	1.97	50	7.48	7.52	11.81
Case	9050B	3.54	90	15.75	15.87	3.54	90	15.75	15.87	22.25
Case	9060B	3.94	100	18.85	18.89	3.94	100	18.85	18.89	22.44
Case	CX 47, 50B	1.77	45		5.98	1.77	45		5.98	10.00
Case	CX 75SR	1.97	50	7.49	7.52	1.97	50	7.49	7.52	11.81
Case	CX130	2.56	65	10.00	10.04	2.56	65	10.00	10.04	15.16
Case	CX135SR	2.56	65	10.00	10.04	2.56	65	10.00	10.04	15.16
Case	CX160	3.15	80	11.81	11.85	3.15	80	11.81	11.85	17.12
Case	CX210	3.15	80	12.05	12.09	3.15	80	12.05	12.09	17.71
Case	CX225SR	3.15	80	12.05	12.09	3.15	80	12.05	12.09	17.71
Case	CX240	3.54	90	12.80	12.83	3.54	90	12.80	12.83	19.29
Case	CX290	3.54	90	12.80	12.83	3.54	90	12.80	12.83	19.29
Case	CX330	3.54	90	15.76	15.79	3.54	90	15.76	15.79	21.06
Case	CX460	3.94	100	18.87	18.90	3.94	100	18.87	18.90	22.44
Case	CX800	5.12	130	22.69	22.72	5.12	130	22.76	22.72	26.57
Caterpillar	305CR	1.58	40	6.26	6.26	1.58	40	6.26	6.26	9.00
Caterpillar	307C	1.77	45	7.28		1.77	45	7.28		12.05
Caterpillar	311C	2.56	65	8.66	8.70	2.56	65	8.66	8.70	16.03
Caterpillar	312B	2.56	65	8.66	8.70	2.56	65	8.66	8.70	16.03
Caterpillar	312C L	2.56	65	8.66	8.70	2.56	65	8.66	8.70	
Caterpillar	314C LCR	2.56	65	8.66	8.70	2.56	65	8.66	8.70	16.03
Caterpillar	315B & 315B L	2.76	70	11.02	11.06	2.76	70	11.02	11.06	18.23
Caterpillar	315C L	2.76	70	11.02	11.06	2.76	70	11.02	11.06	18.23

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Caterpillar	318B L	3.15	80	12.18	12.24	3.15	80	12.18	12.24	17.52
Caterpillar	320B W/ B LINK	3.15	80	12.18	12.24	3.15	80	12.18	12.24	17.52
Caterpillar	320B W/ C LINK	3.15	80	13.77	13.82	3.15	80	13.77	13.82	19.10
Caterpillar	320C W/ B LINK	3.15	80	12.18	12.24	3.15	80	12.18	12.24	17.52
Caterpillar	320C W/ C LINK	3.15	80	13.77	13.82	3.15	80	13.77	13.82	19.10
Caterpillar	322B W/ B LINK	3.15	80	12.18	12.24	3.15	80	12.18	12.24	17.52
Caterpillar	322C W/ B LINK	3.15	80	12.18	12.24	3.15	80	12.18	12.24	17.52
Caterpillar	325B W/ C LINK	3.15	80	13.77	13.82	3.15	80	13.77	13.82	19.10
Caterpillar	325B W/ D LINK	3.54	90	15.16	15.20	3.15	80	15.16	15.20	19.10
Caterpillar	325C W/ C LINK	3.15	80	13.77	13.82	3.15	80	13.77	13.82	19.10
Caterpillar	325C W/ D LINK	3.54	90	15.16	15.20	3.15	80	15.16	15.20	19.10
Caterpillar	330B W/ D LINK	3.54	90	15.16	15.20	3.15	80	15.16	15.20	19.10
Caterpillar	330B W/ E LINK	3.94	100	16.72	16.77	3.15	80	16.72	16.77	21.88
Caterpillar	330C W/ D LINK	3.54	90	15.16	15.20	3.15	80	15.16	15.20	19.10
Caterpillar	330C W/ E LINK	3.94	100	16.72	16.77	3.15	80	16.72	16.77	21.88
Caterpillar	330D W/ D LINK	3.54	90	15.16	15.20	3.15	80	15.16	15.20	19.10
Caterpillar	365B L V Link	4.33	110	19.68	19.75	3.54	90	19.68	19.75	24.80
Caterpillar	375	5.11	130	21.65	21.69	3.94	100	21.65	21.69	21.69
Caterpillar	375CL	5.12	130		25.63	4.33	110		25.63	25.56
Caterpillar	385B L									
Caterpillar	416D	1.97	50	10.00	10.06	1.77	45	8.00	8.27	13.68
Caterpillar	420D	1.97	50	10.04	10.09	1.77	45	8.09	8.27	13.68
Caterpillar	430D	1.97	50	10.04		1.77	45	8.27		13.68
Caterpillar	446B	2.36	60		8.45	2.36	60		8.45	16.87
Caterpillar	308C	1.77	45	7.28		1.77	45	7.28		12.05
Caterpillar	320D W/B LINK	3.15	80	12.18	12.24	3.15	80	12.18	12.24	17.52
Caterpillar	416E	1.97	50	10.00	10.06	1.77	45	8.00	8.27	13.68
Caterpillar	304C CR	1.77	45	6.12	6.14	1.77	45	6.12	6.14	10.23
Caterpillar	305C CR	1.77	45	6.12	6.14	1.77	45	6.12	6.14	10.23
Caterpillar	345C W/TB LINK	4.33	110	17.32	17.36	3.94	100	17.32	17.36	23.11
Caterpillar	365B L VB Link	4.72	120	19.68	19.75	4.33	110	19.68	19.75	24.80
Caterpillar	330D L W/ DB LINK	3.93	100	15.20	15.20	3.93	100	15.20	15.20	19.69
Coyote	C 16LB									
Daewoo	SOLAR 250LC-V	3.15	80	12.09		3.15	80	12.09		
Daewoo	SOLAR 255LC-V	3.15	80	13.15	13.15	3.15	80	13.15	13.15	18.23
Daewoo	SOLAR 290LC-V	3.54	90	15.51		3.54	90	15.59		19.99

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Daewoo	SOLAR 300LC-V SLR	3.54	90	15.51	15.59	3.54	90	15.51	15.59	20.16
Daewoo	SOLAR 330LC-V	3.94	100	16.14		3.94	100	16.14		21.92
Daewoo	SOLAR 340LC-V	3.94	100	16.14		3.94	100	16.14		21.92
Daewoo	SOLAR 400LC-V	4.33	110	17.32	17.40	4.33	110	17.32	17.40	21.06
Daewoo	SOLAR 420LC-V	4.33	110	17.32	17.40	4.33	110	17.32	17.40	
Daewoo	SOLAR 450LC-V	4.72	120	18.50	18.58	4.72	120	18.50	18.58	23.61
Daewoo	SOLAR 470LC-V	4.72	120	18.58		4.72	120	18.58		27.59
Daewoo	DX 300 LC	3.54	90	15.51	15.51	3.54	90	15.51	15.51	19.99
Daewoo	DX 340 LC	3.94	100	16.06	16.14	3.94	100	16.06	16.14	21.65
Daewoo	DX 420 LC	4.33	110	17.32	17.32	4.33	110	17.32	17.32	21.06
Daewoo	DX 480 LC	4.72	120	18.50	18.58	4.72	120	18.50	18.58	22.67
Daewoo	SOLAR 55 V PLUS	1.77	45	6.10	6.10	1.77	45	6.10	6.10	10.13
Daewoo	SOLAR 75 V									
Daewoo	SOLAR 130LC-V	2.56	65	10.24	10.31	2.56	65	10.24	10.31	15.24
Daewoo	SOLAR 140LC-V	2.56	65		10.24	2.56	65		10.24	15.19
Daewoo	SOLAR 170LC-V	3.15	80	12.01	13.15	3.15	80	12.01	13.15	18.27
Daewoo	SOLAR 175LCV	3.15	80		13.15	3.15	80		13.15	18.27
Daewoo	SOLAR 220LC-V	3.15	80	12.01	12.09	3.15	80	12.01	12.09	18.27
Daewoo	SOLAR 225LC-V	3.15	80		13.25	3.15	80		13.25	18.27
Daewoo	SOLAR 225NLC-V	3.15	80		13.25	3.15	80		13.25	18.27
Daewoo	SOLAR 225SLR	3.15	80		13.25	3.15	80		13.25	18.27
Earthforce	EF600									
Gehl	GE 502	1.97	50	7.68		1.97	50	7.68		9.29
Gehl	GE 602	1.97	50	7.68		1.97	50	7.68		9.29
Gehl	GE 802	2.17	55	6.69		2.17	55	6.69		11.81
Gehl	GE1202									
Gehl	GE 503Z	1.97	50	7.68		1.97	50	7.68		9.45
Gehl	GE 803	2.17	55	6.69	6.99	2.17	55	6.69	6.69	11.81
Hitachi	EX 50U	1.77	45	6.29	6.35	1.77	45	6.29	6.35	
Hitachi	EX 110-5	2.56	65	10.00	10.04	2.56	65	10.00	10.04	14.25
Hitachi	Zaxis 50U	1.77	45	6.30	6.33	1.77	45	6.30	6.33	9.05
Hitachi	Zaxis 80	1.97	50	7.87	7.97	1.97	50	7.87	7.97	12.20
Hitachi	Zaxis 120	2.56	65	10.00		2.56	65	10.00		14.25
Hitachi	Zaxis 135US	2.56	65	10.00	10.10	2.56	65	10.00	10.10	14.25
Hitachi	Zaxis 160	3.15	80	12.01	12.09	3.15	80	12.01	12.09	15.80
Hitachi	Zaxis 200 & LC	3.15	80	12.01	12.09	3.15	80	12.01	12.09	18.58

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Hitachi	Zaxis 225US LC	3.15	80	12.01	12.09	3.15	80	12.01	12.09	18.58
Hitachi	Zaxis 230 & LC	3.54	90	16.06	16.14	3.54	90	16.06	16.14	18.70
Hitachi	Zaxis 270LC	3.54	90	16.10	16.14	3.54	90	16.10	16.14	18.70
Hitachi	Zaxis 330 & LC	3.94	100	16.46	16.54	3.94	100	16.46	16.54	23.03
Hitachi	Zaxis 370	3.94	100	16.46	16.54	3.94	100	16.46	16.54	23.03
Hitachi	Zaxis 450 & LC	4.33	110	18.50		4.33	110	18.50		22.36
Hitachi	Zaxis 600LC & BE	4.72	120	20.12		4.72	120	20.12		24.41
Hitachi	Zaxis 800 & BE	5.12	130	21.93		5.12	130	21.93		26.61
Hitachi	Zaxis 850LC-3	5.12	130	21.93		5.12	130	21.93		26.61
Hitachi	Zaxis 350LC-3	3.94	100	16.46	16.54	3.94	100	16.46	16.54	23.03
Hitachi	Zaxis 650LC	4.72	120	20.12		4.72	120	20.12		24.41
Hitachi	Zaxis 350LC	3.94	100	16.46	16.54	3.94	100	16.46	16.54	23.03
Hitachi	Zaxis 75US	1.97	50	7.87	7.97	1.97	50	7.87	7.97	12.20
Hyundai	R290LC-3	3.15	80	15.67	15.75	3.15	80	15.67	15.75	20.08
Hyundai	R290LC-3LR	3.15	80	15.67	15.75	3.15	80	15.67	15.75	20.08
Hyundai	R290LC-7									
Hyundai	R320LC-3	3.94	100	16.92	17.01	3.94	100	16.92	17.01	21.65
Hyundai	R320LC-7, NLC-7, LC-7 HC									
Hyundai	R360LC-3	3.94	100	16.92	17.01	3.94	100	16.92	17.01	21.65
Hyundai	R360LC-7									
Hyundai	R450IC-7	3.94	100		17.00	3.94	100		17.00	22.72
Hyundai	R 55-3	1.77	45	6.45	6.49	1.77	45	6.45	6.49	9.05
Hyundai	R140LC-7	2.56	65	10.16	10.24	2.56	65	10.16	10.24	15.35
Hyundai	R160LC-3	2.76	70	12.04	12.13	2.76	70	12.04	12.13	16.14
Hyundai	R180LC-3	2.76	70	12.05	12.13	2.76	70	12.05	12.13	16.14
Hyundai	R210LC-7	3.15	80		13.07	3.15	80		13.07	18.11
Hyundai	R250LC-3	3.15	80	15.60	15.74	3.15	80	15.60	15.74	20.08
Hyundai	R110LC-7									
Hyundai	R250LC-7	3.54	90	15.60	15.75	3.54	90	15.60	15.75	20.08
IHI	45NX	1.77	45	5.91	5.91	1.77	45	5.91	5.91	
IHI	55J	1.97	50	6.30	6.30	1.97	50	6.30	6.30	9.29
IHI	70Z	1.97	50	6.30	6.30	1.97	50	6.30	6.30	9.39
IHI	80NX	1.97	50	6.30		1.97	50	6.30		9.27
Ingersoll-Rand	ZX125	1.97	50	8.70	8.71	1.97	50	8.70	8.71	11.41
JCB	210S SERIES 2	1.18	30	6.50	6.62	1.18	30	6.50	6.50	
JCB	212S SERIES 2	1.18	30	6.50	6.62	1.18	30	6.50	6.62	9.12

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
JCB	217									
JCB	217S	1.77	45	6.50		1.77	45	6.50		
JCB	8052									
JCB	8080 ZTS	1.77	45		6.75	1.77	45		6.75	14.00
JCB	JS 70									
JCB	JS130	2.56	65	10.04	10.04	2.56	65	10.04	10.04	15.16
JCB	JS160	3.15	80	11.85	11.85	3.15	80	11.85	11.85	17.13
JCB	JS260									
JCB	JS330									
JCB	JS450, JS460									
John Deere	350D LC	3.94	100	16.46	16.54	3.94	100	16.46	16.54	23.03
John Deere	370C	3.94	100	16.46	16.54	3.94	100	16.46	16.54	23.03
John Deere	410G STD OR EXT STICK	2.17	55		8.15	1.97	50		8.15	11.97
John Deere	315SG	2.16	55		8.15	1.96	50		8.15	11.97
John Deere	50ZTS									
John Deere	80C	1.97	50	7.87	7.97	1.97	50	7.87	7.97	12.20
John Deere	120C	2.56	65	10.00		2.56	65	10.00		14.25
John Deere	135C RTS	2.56	65	10.00	10.10	2.56	65	10.00	10.10	14.25
John Deere	160C LC	3.15	80	12.00	12.09	3.15	80	12.00	12.09	15.39
John Deere	200C LC	3.15	80	12.00	12.09	3.15	80	12.00	12.09	18.58
John Deere	225C LC RTS	3.15	80	12.01	12.09	3.15	80	12.01	12.09	18.74
John Deere	240D LC	3.54	90	16.08	16.14	3.54	90	16.08	16.14	18.70
John Deere	270D LC	3.54	90	16.08	16.14	3.54	90	16.08	16.14	18.70
John Deere	310G STD or EXT Stick	1.77	45		8.15	1.52			8.14	13.39
John Deere	310SG STD or EXT Stick	2.15	55		8.15	1.95			8.15	11.97
John Deere	450D LC	4.33	110	18.50	18.58	4.33	110	18.50	18.58	22.52
John Deere	600C LC & ME	4.72	120	20.12		4.72	120	20.12		24.41
John Deere	650D LC									
John Deere	710G STD or EXT Stick	2.48	63	8.75	8.88	2.48	63	8.50	8.88	13.10
John Deere	800 C & ME	5.12	130	21.93		5.12	130	21.93		26.61
John Deere	850D LC									
John Deere	710J STD or EXT Stick	2.48	63	8.75	8.88	2.48	63	8.50	8.88	13.10
John Deere	75C	1.97	50	7.87	7.97	1.97	50	7.87	7.97	12.20
John Deere	410J	2.17	55	8.15	8.15	1.97	50	8.15	8.15	11.97
John Deere	200D LC	3.15	80	12.00	12.09	3.15	80	12.00	12.09	18.58
Kobelco	45SR-2	1.77	45		5.97	1.77	45		5.97	10.00

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Kobelco	70SR	1.97	50	7.09	7.17	1.97	50	7.09	7.17	11.42
Kobelco	80CS	1.97	50	7.09	7.17	1.97	50	7.09	7.17	11.42
Kobelco	115SRDZ	2.56	65	9.84	9.92	2.56	65	9.84	9.92	16.53
Kobelco	135SRLC	2.56	65	9.84	9.92	2.56	65	9.84	9.92	16.53
Kobelco	200SR LC	3.15	80		12.87	3.15	80		12.87	17.40
Kobelco	235SRLC	3.15	80	12.80		3.15	80	12.80		17.40
Kobelco	ED180	2.76	70	11.81	11.89	2.76	70	11.81	11.89	16.18
Kobelco	ED190	2.76	70	11.81	11.88	2.76	70	11.81	11.88	16.81
Kobelco	SK 160LC	2.76	70	11.81	11.88	2.76	70	11.81	11.81	16.18
Kobelco	SK 210LC-VI	3.15	80	12.80	12.88	3.15	80	12.80	12.88	17.40
Kobelco	SK 250LC	3.54	90	12.80	12.88	3.54	90	12.80	12.88	20.23
Kobelco	SK 290LC	3.55	90	14.96	15.04	3.55	90	14.96	15.04	20.74
Kobelco	SK 330LC	3.55	90	14.96	15.04	3.55	90	14.96	15.04	21.03
Kobelco	SK 480	3.94	100	17.71	17.73	3.94	100	17.71	17.73	24.80
Kobelco	SK480 LC									
Kobelco	50SR-3	1.77	45		5.97	1.77	45		5.97	10.00
Kobelco	SK 350LC	3.55	90	14.96	15.04	3.55	90	14.96	15.04	21.03
Komatsu	PC 40MR-2	1.77	45	6.71	6.72	1.77	45	6.71	6.72	9.07
Komatsu	PC 50MR-2	1.77	45	6.61	6.72	1.77	45	6.61	6.72	9.07
Komatsu	PC 60-7	1.97	50	7.85	7.87	1.97	50	7.85	7.87	12.29
Komatsu	PC 75R-2	1.97	50		6.38	1.97	50		6.38	
Komatsu	PC 78MR-6	1.97	50	7.87	7.90	1.97	50	7.87	7.90	12.29
Komatsu	PC 95R-2	1.97	50	7.40	7.87	7.97	202	7.40	7.87	12.29
Komatsu	PC 100-6	2.36	60	10.23	10.31	2.36	60	10.23	10.31	14.76
Komatsu	PC 120-6	2.36	60	10.23	10.31	2.36	60	10.23	10.31	14.76
Komatsu	PC 128US-2	2.36	60	8.90	10.79	2.36	60	10.20	10.28	14.76
Komatsu	PC 128UU-2	2.36	60	10.23	10.31	2.36	60	10.23	10.31	14.76
Komatsu	PC 138USLC-2	2.36	60	8.90	10.79	2.36	60	10.20	10.28	14.76
Komatsu	PC 150-6	2.76	70	12.20	12.25	2.76	70	12.20	12.25	15.78
Komatsu	PC 158USLC-2	2.36	60	10.16	10.79	2.36	60	10.15	10.28	14.76
Komatsu	PC 160LC-7	2.76	70	12.20	12.25	2.76	70	12.20	12.25	15.78
Komatsu	PC 200-6	3.15	80	12.79	12.90	3.15	80	12.79	12.90	18.04
Komatsu	PC 200-7	3.15	80	12.79	12.90	3.15	80	12.79	12.90	18.04
Komatsu	PC 200LC-8	3.15	80	12.79	12.90	3.15	80	12.79	12.90	18.04
Komatsu	PC 210-6	3.15	80	12.79	12.90	3.15	80	12.79	12.90	18.04
Komatsu	PC 220LC-6	3.15	80	12.79	12.89	3.15	80	12.79	12.89	17.57

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Komatsu	PC 220LC-7	3.15	80	12.79	12.89	3.15	80	12.79	12.89	17.57
Komatsu	PC 220LC-8	3.15	80	12.79	12.90	3.15	80	12.79	12.90	17.57
Komatsu	PC 228USLC-1	3.15	80	12.79		3.15	80	12.79		18.04
Komatsu	PC 228USLC-2	3.15	80	12.79		3.15	80	12.79		18.04
Komatsu	PC 228USLC-3	3.15	80	12.79		3.15	80	12.79		18.04
Komatsu	PC 250-6	3.15	80	12.79	12.89	3.15	80	12.79	12.89	17.57
Komatsu	PC 270LC-6	3.15	80	12.79	12.89	3.15	80	12.79	12.89	17.57
Komatsu	PC 270LC-7	3.15	80	12.79	12.89	3.15	80	12.79	12.89	17.57
Komatsu	PC 300-6	3.54	90	13.50	13.62	3.54	90	13.50	13.62	20.22
Komatsu	PC 300HD-6	3.54	90	13.62		3.54	90	13.58		
Komatsu	PC 300LC-7	3.54	90	13.50	13.62	3.54	90	13.50	13.62	20.22
Komatsu	PC 308USLC-3	3.15	80	12.79		3.15	80	12.79		17.57
Komatsu	PC 400-7	3.94	100	14.56	14.61	3.94	100	14.56	14.61	21.14
Komatsu	PC 400HD-6									
Komatsu	PC 600LC-6	4.53	115	18.25	18.30	4.53	115	17.95	18.00	23.89
Komatsu	PC 600LC-7	4.53	115	18.25	18.30	4.53	115	17.95	18.00	23.89
Komatsu	PC 600LC-8	4.53	115	18.25	18.30	4.53	115	17.95	18.00	23.89
Komatsu	PC 750-6	5.12	130	21.06	22.03	4.53	115	20.43	20.47	29.76
Komatsu	WB140-2 STD & EXT Arm	1.58	40	6.30	6.38	1.58	40	6.30	6.38	11.61
Komatsu	WB146-5, PS-5	1.97	50	6.38	6.38	1.77	45	6.38	6.38	11.61
Komatsu	WB150-2 STD & EXT Arm	1.58	40	6.30	6.38	1.58	40	6.30	6.38	11.61
Komatsu	PC 800LC-7	5.12	130	21.06	22.03	4.53	115	20.43	20.47	29.76
Komatsu	PC 400-8	3.94	100	14.56	14.61	3.94	100	14.56	14.61	21.14
Kramer-Allrad	316 Series 2	1.58	40	6.38		1.58	40	6.22		
Kramer-Allrad	616S	1.97	50	7.20		1.97	50	7.20		10.82
Kubota	KX161-2S	1.77	45			1.77	45			9.57
Kubota	KX161-3	1.77	45	5.71		1.77	45	5.71		9.62
Kubota	U45	1.77	45	5.71		1.77	45	5.71		9.62
Kubota	KX080-3	2.36	60	7.88	7.90	2.36	60	7.88	7.90	11.82
Link-Belt	75SA (Mono & Offset)	1.97	50	7.48	7.52	1.97	50	7.48	7.52	11.81
Link-Belt	80SA	1.97	50	7.48	7.52	1.97	50	7.48	7.52	11.81
Link-Belt	130LX	2.56	65	10.00	10.04	2.56	65	10.00	10.04	15.16
Link-Belt	135SA	2.56	65	10.00	10.04	2.56	65	10.00	10.04	15.16
Link-Belt	160LX	3.15	80	11.81	11.85	3.15	80	11.81	11.85	17.12
Link-Belt	210LX	3.15	80	12.05	12.09	3.15	80	12.05	12.09	17.76
Link-Belt	225SA	3.15	80	12.05	12.09	3.15	80	12.05	12.09	17.51

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Link-Belt	240LX	3.54	90	12.79	12.83	3.54	90	12.79	12.83	18.11
Link-Belt	290LX	3.54	90	12.80	12.83	3.54	90	12.80	12.83	18.11
Link-Belt	330LX	3.54	90	15.74	15.79	3.54	90	15.74	15.79	21.06
Link-Belt	460LX	3.94	100	18.86	18.90	3.94	100	18.86	18.90	22.44
Link-Belt	800LX	5.12	130	22.68	22.72	5.12	130	22.68	22.72	26.57
Link-Belt	1600 QUANTUM	1.97	50	7.48	7.52	1.97	50	7.48	7.52	11.81
Link-Belt	2650 QUANTUM	2.56	65	10.00	10.06	2.56	65	10.00	10.06	15.16
Link-Belt	2700 QUANTUM	3.15	80	11.81	11.85	3.15	80	11.81	11.85	17.13
Link-Belt	2800 QUANTUM	3.15	80	12.05	12.09	3.15	80	12.05	12.09	17.32
Link-Belt	3400 QUANTUM	3.54	90	12.79	12.83	3.54	90	12.79	12.83	18.11
Link-Belt	3900 QUANTUM	3.54	90	12.79	12.84	3.54	90	12.79	12.84	18.11
Link-Belt	4300 QUANTUM	3.54	90	15.79	15.87	3.54	90	15.79	15.87	22.24
Link-Belt	5800 QUANTUM	3.94	100	18.85	18.89	3.94	100	18.85	18.89	22.44
Link-Belt	8000 QUANTUM	5.12	130	22.68	22.72	5.12	130	22.68	22.72	26.57
Link-Belt	8000 QUANTUM MASS	5.12	130	22.68	22.72	5.12	130	22.68	22.72	26.57
Link-Belt	160X2	3.15	80	11.81	11.85	3.18	81	11.81	11.85	17.12
Liebherr	R308	2.36	60	8.66		2.36	60	8.66		
Liebherr	R900B LITRONIC	2.36	60	10.87	11.08	2.36	60	10.87	11.08	12.99
Liebherr	R904 LITRONIC	2.76	70	12.12	12.12	2.36	60			14.56
Liebherr	R914 LITRONIC	3.15	80	13.70		2.76	70	13.70		16.53
Liebherr	R924 LITRONIC	3.15	80	13.70		2.76	70	13.70		16.53
Liebherr	R934 LITRONIC	3.15	80	20.00		2.76	70	20.00		16.54
Liebherr	R944 LITRONIC	3.15	80	21.57	21.61	3.15	80	21.57	21.61	17.72
Liebherr	R954 LITRONIC									
Liebherr	R954B LITRONIC									
Liebherr	R964B LITRONIC									
Liebherr	R974 LITRONIC									
Liebherr	R974B LITRONIC									
Liebherr	R984 LITRONIC									
Liebherr	R984B LITRONIC									
Melroe	PC 400-6	3.94	100	14.56	14.61	3.94	100	14.56	14.61	21.14
Mustang	ME 5002	1.97	50	7.68		1.97	50	7.68		9.29
Mustang	ME 6002 & ME 6502	1.97	50	7.68		1.97	50	7.68		9.29
Mustang	ME 8002	2.17	55	6.69		2.17	55	6.69		11.81
Mustang	ME12002	2.36	60	8.66		2.36	60	8.66		13.18
New Holland	LB 75	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35



Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
New Holland	LB 75B	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35
New Holland	LB 90	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35
New Holland	LB110	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35
New Holland	LB115, B	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35
New Holland	B 95, TC, LR	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35
New Holland	B110	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35
New Holland	B115	1.77	45	7.87	8.03	1.77	45	7.87	8.03	15.35
New Holland	EC 45	1.58	40		6.34	1.58	40		6.34	9.84
New Holland	EH 50.B	1.77	45	5.98	5.98	1.77	45	5.98	5.98	10.00
New Holland	EH130	2.56	65	9.84	9.92	2.56	65	9.84	9.92	16.53
New Holland	EH160	2.76	70	11.81	11.88	2.76	70	11.81	11.88	16.18
New Holland	EH215	3.15	80	12.80	12.88	3.15	80	12.80	12.88	17.40
Scattrak	254S	1.58	40		7.09	1.58	40		7.09	
Schaeff	HR 18									
Schaeff	HR 22									
Schaeff	HR 32	1.97	50	7.28	7.28	1.97	50	7.28	7.28	10.82
Schaeff	HR 41									
Schaeff	HS 41 M									
Takeuchi	TB070	1.97	50	6.50	6.57	1.97	50	6.50	6.57	11.53
Takeuchi	TB145	1.77	45		5.91	1.77	45		5.91	9.19
Takeuchi	TB175	1.97	50	6.50	6.57	1.97	50	6.50	6.57	11.53
Takeuchi	TB53R	1.77	45		5.91	1.77	45		5.91	9.19
Takeuchi	TB1140	2.56	65	10.00	10.00	2.56	65	10.00	10.00	14.25
Terex	HR18	1.58	40	6.34	6.34	1.58	40	6.34	6.34	9.84
Terex	HR32	1.97	50	7.28	7.28	1.97	50	7.28	7.28	10.82
Terex	HR42	1.97	50			1.97	50			11.42
Terex	TX750	1.77	45		7.12	1.77	45		7.12	14.17
Terex	TX760	1.77	45		7.12	1.77	45		7.12	14.17
Terex	TX860	1.77	45		7.12	1.77	45		7.12	14.17
Terex	TX860SB									
Terex	TX960									
Terex	TX965									
Terex	TXC 140LC-1	2.56	65		10.24	2.56	65		10.24	15.19
Terex	TXC 225LC	3.15	80		13.25	3.15	80		13.25	18.27
Terex	TXC 255LC	3.15	80	13.15	13.15	3.15	80	13.15	13.15	18.23
Terex	TXC 175LC	3.15	80		13.15	3.15	80		13.15	18.27

Manufacturer	Model	Stick Pin Diameter (Inch)	Stick Pin Diameter (mm)	Stick Width (Inch)	Bucket Width at Stick (Inch)	Link Pin Diameter (Inch)	Link Pin Diameter (mm)	Link Width (Inch)	Bucket Width at Link (Inch)	Pin Centers (Inch)
Terex	TXC 180LC	3.15	80		13.15	3.15	80		13.15	18.27
Volvo	BL70	1.77	45	6.50	6.62	1.77	45	6.50	6.62	12.00
Volvo	EC 55, B	1.77	45	6.46	6.50	1.77	45		6.50	11.22
Volvo	EC140B	2.56	65	10.78	10.82	2.56	65	10.78	10.82	14.96
Volvo	EC160B	2.76	70	11.38	11.38	2.76	70	11.38	11.38	17.32
Volvo	EC210B	3.15	80	12.79	12.83	3.15	80	12.79	12.83	18.38
Volvo	EC240B	3.54	90	15.00		3.54	90	14.96		19.92
Volvo	EC290B	3.54	90	16.14		3.54	90			19.48
Volvo	EC330B	4.33	110	17.32		3.94	100			22.44
Volvo	EC360B	4.33	110	17.32		3.94	100			22.44
Volvo	EC460B	4.33	110	18.50		3.94	100			22.44
Volvo	ECR 88	2.36	60		6.78	2.36	60		6.78	11.42
Volvo	ECR 58	1.77	45	6.26	6.34	1.77	45	6.26	6.34	11.22
Volvo	EC700B	4.72	120	20.08		4.72	120	18.90		24.80
Yanmar	B 7-3	1.97	50	7.87		1.97	50	7.87		12.29
Yanmar	B50-2B	1.77	45	6.06	6.10	1.77	45	6.06	6.10	10.63
Yanmar	B7 SIGMA	1.97	50	7.80	7.87	1.97	50	7.80	7.87	12.28
Yanmar	VIO50-2	1.77	45		6.49	1.77	45		6.49	10.63
Yanmar	VIO70	1.97	50	7.87	7.87	1.97	50	7.87	7.87	12.29
Yanmar	VIO75	1.97	50	7.87	7.90	1.97	50	7.87	7.90	12.28
Yanmar	VIO45-5	1.77	45	6.49	6.49	1.77	45	6.49	6.49	10.63
Yanmar	VIO 55-5	1.77	45	6.49	6.49	1.77	45	6.49	6.49	10.63